

TN Normae Series

Handheld Thermal Binoculars



Introduce

TN Normae Series follows classic binocular design, greatly reducing the fatigue feeling of long-time observation. It adopts high-sensitivity VOx uncooled IR detector, bring you high quality imaging and immersive observation experience with full color OLED 1024×768 high-definition display. A variety of functions to meet all your needs, such as taking photos, videos, WIFI, laser ranging, GPS, compass, etc.



Features and Benefits

- IR resolution up to 640 × 480, Superior image quality
- Quick location, laser ranger finder with 600m accuracy
- Full color OLED 1024×768 high-definition display, easy observation
- Adjustable interpupillary distance between 60mm~70mm
- Well-designed PIP mode, highlighting the target
- Realize live image and remote control via WIFI connection


Application

- Night hunting
- Law enforcement
- Search & Rescue
- Personal security



Specifications

Model	TN430	TN450	TN630	TN650	
Detector					
Detector Type	400×3	600 @17μm, VOx		640×480@12μm, VOx	
Spectral	8μm~14μm				
NETD			≤50mk		
_ens					
Focal Length	35mm/F1.2	50mm/F1.2	2 35mm/F1	1.2 50mm/F1.2	2
FOV	11.1°×8.3°	7.8°×5.8°	· ·		
Focusing	11.1 0.0	7.0 0.0	Manual Focus	5 0.0 0.0	
Display			Warraar r ocas		
Screen		Full-color 0	39'OLED Screen ×2, 1024×7	768	
	Exit pupil distance 16.4mm, Adjustable diopter -4~ + 2, Adjustable interpupillary distance				
Eyepiece	between 60mm~70mm				
Magnification	2.3X~9.2X	3.2X~12.8X	2.0X~16	X 2.8X~22.4	Χ
maging				'	
Frame Rate			50Hz		
Digital Zoom	1X~4X (Smooth zoom) 1X~8X (Smooth zoom)				
Color Palettes	White Hot, Black Hot, Customized red hot, Blue Hot, Red Hot, Green hot				
Scenes Modes	Enhanced, Highlight, Natural				
Picture-in-picture	Dicture in ni		, , , ,	upper middle or upper right	
·	Ficture-in-pr	cture emarged image is	aispidyed on the upper left,	apper middle or apper right	
Functions					
Photo	√	√	√	√	
Video	√	√	√	√	
Hotspot Tracking	√	√	√	√	
Laser Designating	Red Yellow Green				
Laser Ranging	Single ranging or continuous ranging				
Wi-Fi/APP	Wi-Fi share photo and video, also can controlled by App(IOS & Android)				
Compensation Modes	Auto Compensation / Shutter Compensation / Scene Compensation				
Other	Smooth Mag			rast of image are adjustable,	
Power Supply		GPS, COMP	ass, Gyroscope, Bluetooth, e	it.	
,		Pomovable 9	Standard 194EO Licion hattor	27.72	
Battery Type	Removable Standard 18650 Li-ion battery x2				
Working Time			≥6h		
nterface		TVDE C (LICD 2.0 -+-	maland \ fan alamaia a Data	An and desired	
USB	TYPE C (USB 2.0 standard) for charging, Data tranmission				
Video Output	Micro HDMI				
Tripod Interface	Inch 1/4-20				
Memory Card		Built-in 16G	GB SD card,Max. support 128	8G	
Environmental Characteristics	3				
Operating Temperature	-30°C ~ 50°C				
Storage Temperature	-40°C ~ 60°C				
Encapsulation	IP66, 1-meter drop test				
Certificate		UN38.3 (Batter	ry certificate), RoHS, CE, FCC	C, EAC	
Weight & Dimensions					
Weight	860g	880g	860g	880g	
Dimensions		16	2mm×146mm×70mm		
Package Contents					
Standard	Power adapter, Type-C USB cable, Micro HDMI cable, Lens cover, Wrist strap, Removable shading eye blinders x2,Portable package, Quick Start Guide				
		Hand shank	c, Picatinny rail, Remote Con	trol	
Optional					
'	_				
Optional Detection Range Recognition Range					Unit
'	ge TN430	TN450	TN630	TN650	Unit
Detection Range Recognition Range	TN430	TN450		TN650	Unit
'			TN630 1400 700		Unit
Detection Range Recognition Range	TN430	1400	700	1000 2000	Unit 3300



Guide Sensmart Tech Co., Ltd. Loeffelholzstrasse 20, Haus 12 Eingang Nord, 90441 Nuremberg, Germany Email: enquiry@guide-infrared.com



